

Model 2914-4 Very-Low-Power Bandpass Filter for IBOC

Performance Specifications:

Type:	Resonant Cavity	
Size:	3"	
No. of Cavities:	4	
Typical VSWR	at ± 100 kHz:	1.06:1
	at ± 150 kHz:	1.05:1
	at ± 200 kHz:	1.08:1
Typical Insertion Loss:	-1.65 dB	
Typical Frequency Response (deviation from center frequency)	at ± 100 kHz:	-0.08 dB
	at ± 150 kHz:	-0.15 dB
	at ± 200 kHz:	-0.20 dB
Typical Group Delay (deviation from center frequency)	at ± 100 kHz:	25 nsec
	at ± 150 kHz:	50 nsec
	at ± 200 kHz:	150 nsec
Typical Bandwidth:	± 200 kHz	

Inputs, Outputs, and Weight:

Inputs:	Type "N" Female
Outputs:	Type "N" Female
Maximum Input Power:	500 W
Cooling:	Convection
Shipping Weight:	37 lb (16.8 kg)
Dimensions:	48" (121.9 cm) H
	4" (10.2 cm) D
	16" (40.6 cm) W



Document No. ds-2914-4_iboc (090520)

A Division of Howell Laboratories, Inc., P. O. Box 389, Bridgton, Maine 04009 USA
 (207) 647-3327 1-888-SHIVELY Fax: (207)647-8273
 An Employee-Owned Company

www.shively.com
 sales@shively.com
 Certified to ISO-9001:2000