

## Model 2930 Two- and Three-Station Low-Power Branched Combiners

	Model 2930-2/3	Model 2930-2/4	Model 2930-3/3	Model 2930-3/4
No. of Stations:	2	2	3	3
Frequency Spacing:	≥ 0.8 MHz	≥ 0.8 MHz	≥ 0.8 MHz	≥ 0.8 MHz

### Performance Specifications:

		Model 2930-2/3	Model 2930-2/4	Model 2930-3/3	Model 2930-3/4
Typical VSWR	at ± 100 kHz:	1.06:1		1.06:1	
	at ± 150 kHz:	1.05:1		1.05:1	
	at ± 200 kHz:	1.08:1		1.08:1	
Typical Insertion Loss:		-1.15 dB	-1.5 dB	-1.15 dB	-1.5 dB
Typical Frequency Response (deviation from center frequency)	at ± 100 kHz:	-0.05 dB		-0.05 dB	
	at ± 150 kHz:	-0.15 dB		-0.15 dB	
	at ± 200 kHz:	-0.20 dB		-0.20 dB	
		Model 2930-2/3	Model 2930-2/4	Model 2930-3/3	Model 2930-3/4
Typical Group Delay (deviation from center frequency)	at ± 100 kHz:	20 nsec	25 nsec	20 nsec	25 nsec
	at ± 150 kHz:	40 nsec	50 nsec	40 nsec	50 nsec
	at ± 200 kHz:	100 nsec	150 nsec	100 nsec	150 nsec
Typical Bandwidth:		± 200 kHz		± 200 kHz	
Power Rating:		Per-station limit of 500 W.			



### Description:

	Model 2930-2/3	Model 2930-2/4	Model 2930-3/3	Model 2930-3/4
Type:	Convection-cooled resonant cavity			
Size:	3-inch			
No. of Cavities per Station:	3	4	3	4
Inputs:	Type "N"			
Outputs:	to 1.5 kW: "Type N"; above 1.5 kW: 7-16 DIN			

Document No. ds-2930 (090520)

A Division of Howell Laboratories, Inc., P. O. Box 389, Bridgton, Maine 04009 USA  
 (207) 647-3327 1-888-SHIVELY Fax: (207)647-8273  
 An Employee-Owned Company

www.shively.com  
 sales@shively.com  
 Certified to ISO-9001:2000